e-bin housing PRO 360 L



Frontal door version




Rear door version




manufactured by
Cervic Environment

OUTDOOR

360L Frontal door



360L Rear door



DOOR OPENNING VERSIONS



Front door version



Rear door version



Anti-vandal system
to preserv the pedal drive



Three pedal height adjustments
in back door version



Lector can be placed
on the Top or on the Front



Optional accessory
padlock support and padlock

- Prepared to accommodate Electronic Lock, Access Control & Fill Sensor.
- Lector can be mounted on the top or front of the bin housing (depending on the device's requirements).
- Bin housing suitable to hold a wheelie bin of 360 liters (wheelie bin not included).
- Foot-pedal operated lid with soft-close system (with large & intuitive pedal drive that covers all front to make easier to end user to press it).
- Self-closing lid located at the top of the bin housing (featured with rainproof system and large opening)
- Vandal-proof: Foot-pedal drive with system to prevent intentional breakage of the lid opening system.
- Two door emptying access versions: Frontal Door or Rear Door.
- Door with protected access through two key-locks.
- Door can open to the left or right, configurable by the customer according to location requirements.
- On the rear door version, three pedal height adjustments are available: 90, 150, and 210 mm from the ground. This can be configured on-site by the customer according to the location requirements, making it ideal for placement in the roadway to save the curb step, areas with snow on the ground, etc .
- Compatible with plastic wheelie bins of 360L compliant with UNE 840 standard.
- Accessibility: in the rear door version the height of the lid to deposit the waste is placed less than 1200 mm from the ground (in accordance with accessibility order TMA/851/2021.
- Incorporates waste identification: color, symbol, and name of the waste.
- Robust construction and compact dimensions, with all rounded edges, assembled using concealed rivets and screws that allow for easy replacement of parts in case of damage or breakage.
- Accessory (optional): padlock support and a high-security padlock.
- Opening to deposit measures 420 x 350 mm
- Made of hot-dip galvanized steel sheets of 1, 1.5, and 3 mm thicknesses and hinge elements made of 304 stainless steel.
- Finished with thermosetting polyester powder coating with a zinc-rich anti-corrosive primer applied to thick parts and those with high user or collector contact, such as the pedal, and the manual handle on the user lid.
- Adjustable legs allow for height adjustments of up to 40mm.
- Can be anchored to the ground from inside using four M8 expansion bolts (included).
- Suitable to be used indoor and outdoor under normal weather conditions. In case of extreme weather conditions, such as high salinity, temperature or humidity, an additional special treatment can be applied. Check extra cost and MOQ.



example's installation of rear door version, with the pedal drive at maximum height to save the curb step